

## 大流量管上式压力补偿滴头 On-Line PC Bubblers

## 特点 Features:

- 内置新一代迷宫式宽流道,全程自清洗,进水口带过滤格栅,抗堵塞性能好。
- 采用进口优质硅胶生产膜片,压力补偿效果好;同时稳定性强,使用寿命长。
- 使用100%优质塑料原料和添加剂生产,耐腐蚀,耐老化,抗紫外线强。
- 采用先进生产工艺,制造偏差CV小,确保每个滴头出水均匀。
- 压力补偿效果好, 确保在高低起伏地形也能出水均匀。
- Wide and deep water passageways of labyrinth inside dripper and Continuous self-flushing improve clogging resistance.
- Diaphragm inside dripper made by excellent silicone gel is good for effect of pressure compensation and stability with long service life.
- Produced by Good Quality of Raw plastic materials and additive insure anti-corrosion, anti-UV and anti-aging well.
- Adopting advanced production technology with very low CV, which is sure that the flowing of each dripper is nearly same.
- Uniform discharges as high efficiency of PC, It is good at irrigation for the area of undulating terrain.

## 应用范围 Application:


- 补偿范围1.0-4.0Bar,适用于果树,灌木或园林景观,可替代微喷使用。
- 现有25L/h, 40L/h二种流量选择,满足不同灌溉需求。
- 推荐过滤等级: 120目。
- Recommended filtration: 130 micron/ 120 mesh.
- Two flowing rate available, 25L/h and 40L/h to meet different requirement.
- The range of PC is 1.0-4.0bar. Suitable for field irrigation, shrubbery, fruit tree and landscape.



<sup>\*</sup>备注: 货号后B代表Barb,表示出水口为倒刺接头, 货号后N代表Nipple,表示出水口为承插接头

## 技术参数 Technical Data:

压力 VS 流量表 Pressure VS Flow Rate	工作压力 Working Pressure (Bar)	流量 Flow Rate (L/h)	
		PCD0225B/N	PCD0240B/N
45.0 Q (L/h)	1.0	24.5	40.5
35.0	2.0	26.1	41.0
30.0	3.0	26.4	41.3
25.0	4.0	24.9	40.0
15.0 P (Bar) 1.0 1.5 2.0 2.5 3.0 3.5 4.0	喷洒直径 (m) Spray Diameter	1.1	1.7





<sup>\*</sup>Note: Item No. with "B" means dripper with Barb outlet connection, "N" mean with Nipple connection.